



7.7 Dati tecnici

7.7 Technical data

7.7 Technische Daten7

| L | n ₁ = 1400 | | | LC - LF | | | LA | |
|----|-----------------------|----|-----------------------|----------------------|----------|-----|-----------------------|---------|
| | in | ir | n ₂ rpm | T ₂ Nm | P1 kW | FS' | T _{2M} Nm | P kW |
| 19 | 1 | 1 | 1400 | 12 | 1.8 | 3 | 35 | 5.5 |
| | 2 | 2 | 700 | 24 | 1.8 | 1.7 | 40 | 3 |
| | 3 | 3 | 467 | 36 | 1.8 | 1.2 | 43 | 2.2 |
| 24 | 1 | 1 | 1400 | 26 | 4 | 2.7 | 73 | 11 |
| | 2 | 2 | 700 | 53 | 4 | 1.4 | 72 | 5.5 |
| | 3 | 3 | 467 | 78 | 4 | 1 | 78 | 4 |
| 28 | 1 | 1 | 1400 | 61 | 9.2 | 2.4 | 146 | 22 |
| | 2 | 2 | 700 | 122 | 9.2 | 1.2 | 145 | 11 |
| | 3 | 3 | 467 | 182 | 9.2 | 1 | 182 | 9.2 |

| L | n ₁ = 1400 | | | LC - LF | | | LA | |
|----|-----------------------|----|-----------------------|----------------------|----------|-----|-----------------------|---------|
| | in | ir | n ₂ rpm | T ₂ Nm | P1 kW | FS' | T _{2M} Nm | P kW |
| 38 | 1 | 1 | 1400 | 146 | 22 | 2 | 298 | 45 |
| | 2 | 2 | 700 | 291 | 22 | 1 | 291 | 22 |
| | 3 | 3 | 467 | 297 | 15 | 1 | 297 | 15 |
| 48 | 1 | 1 | 1400 | 199 | 30 | 3 | 596 | 90 |
| | 2 | 2 | 700 | 397 | 30 | 1.5 | 583 | 45 |
| | 3 | 3 | 467 | 597 | 30 | 1 | 597 | 30 |

Verifica termica necessaria / Thermal rating needed / Thermische - Prüfung erforderlich

| L | i | IEC | | | | | | | | | |
|----|-------|---------|----|----|----|-----|-----|-----|-----|-----|-----|
| | | 63 | 71 | 80 | 90 | 100 | 112 | 132 | 160 | 180 | 200 |
| 19 | 1-2-3 | LC - LF | | | | | | | | | |
| 24 | 1-2-3 | LC - LF | | | | | | | | | |
| 28 | 1-2-3 | LC - LF | | | | | | | | | |
| 38 | 1-2-3 | LC - LF | | | | | | | | | |
| 48 | 1-2-3 | LC - LF | | | | | | | | | |

7.8 Senso di rotazione alberi

7.8 Shaft Rotation Direction

7.8 Wellendrehrrichtungen

s.e. = Entrata supplementare / Additional input / Zusatzantrieb

